

LIGHT SCANNING METHOD AND LIGHT SCANNING DEVICE

BACKGROUND OF THE INVENTION

Field of Invention

The present invention relates to a light scanning method and a light scanning device, and more particularly to a light scanning method in a light scanning device which deflects plural light beams emitted from a light source by reflection surfaces of a deflector, and simultaneously main-scans by the plural light beams deflected by the deflector a surface to be scanned, and to a light scanning device.

Description of the Related Art

Image recording apparatuses for recording images by light beams such as laser printers and electronic photocopiers are widely used. In such image recording apparatus, a photosensitive material is scanned by a light beam by means of a light scanning device.

In the light scanning device, generally, the light beam emitted from the semiconductor laser is modulated according to image data, and, via a collimator lens or the like, is incident on the reflection surfaces of a rotary polygonal mirror rotating at a predetermined speed.

By rotation of this rotary polygonal mirror, the light beam is deflected while its incident angle is being changed continuously, and the light beams scans the photosensitive material. The light beam reflected by the reflection surfaces of the rotary polygonal mirror is guided to the photosensitive material via an $f\theta$ lens, a cylinder mirror (or cylinder lens), and the like, and scans the photosensitive material at a constant

speed and is focused on the photosensitive material. As a result, an image is exposed and recorded on the photosensitive material.

Recently, to meet the need for higher speeds of image forming apparatus, improvements in the scanning speed of the light scanning device have been desired. As a technology for improving the speed of a light scanning device, the simultaneous scanning method has been known in which plural scanning lines are scanned simultaneously by one scanning by using plural light beams.

In designing the optical system of the light scanning device of this simultaneous scanning system (hereinafter called plural-beam scanning optical system), the bow difference and pitch deviation between the plural light beams must be considered. Fig.9 shows bow difference occurring in the case of scanning with two light beams, and Fig. 10 shows pitch deviation when scanning with two light beams. In the diagrams, the broken line indicates an ideal scanning line position, and the solid line represents an actual scanning line position.

The bow difference means changes in the interval between two light beams in the subscanning direction depending on the scanning position in the main scanning direction, due to a difference in the curvature of the scanning lines formed by the light beams. The pitch deviation means widening or narrowing of the interval between scanning lines when two light beams are scanned simultaneously in a state in which the interval in the subscanning direction between the light beams deviates from a prescribed value. When scanning plural scanning lines simultaneously in one scanning by using plural light beams, if such bow

the reflection surfaces of the rotary polygonal mirror in the main scanning direction had to be increased substantially.

According to the technology disclosed in Japanese Patent Application Laid-Open (JP-A) No. 5-294005, by disposing beams in a two-dimensional arrangement by using a VCSEL (Vertical Cavity Surface Emitting Laser Diode) as the light source, even if the number of beams is increased, the beams are prevented from greatly moving away from the optical axis of the optical system. However, in the case of the light source having light emission points disposed in a two-dimensional arrangement, unlike the conventional one-row arrangement light source, the interval between light emission points in the subscanning direction cannot be apparently narrowed by inclining the entire light source, and hence it is desired to solve the problems of bow difference and pitch deviation optically. So far, several methods have been proposed for reducing the bow difference or pitch deviation optically.

<Technology for reducing bow difference>

- 1) Using a $f \sin \theta$ lens: JP-A No. 1-163717
- 2) Reducing the subscanning direction lateral magnification rate of an optical system: JP-A No. 2-54211, JP-A No. 9-281421
- 3) Canceling mutual bow differences occurring at plural positions: JP-A No. 2-129614, JP-A No. 8-118725
- 4) Specifying intersecting positions of plural beams: JP-A No. 6-18802, JP-A No. 7-209596, JP-A No. 9-274152
- 5) Limiting tolerance of bow difference: JP-A No. 6-202019
- 6) Balancing subscanning direction image plane curvature and

bow difference: JP-A No. 7-199109

1-180510

7) Using an aspherical lens: JP-A No. 1-180501, JP-A No. 8-297256, JP-A No. 9-33850, JP-A No. 9-146030, JP-A No. 10-333069, JP-A No. 11-84285

8) Aligning plural beams in the bow direction: JP-A No. 10-68898, JP-A No. 10-293260

<Technology for reducing pitch deviation>

1) Making plural beams incident, in parallel, onto the surface to be scanned: JP-A No. 7-209596, JP-A No. 9-274151

Thus, various technologies for reducing either one of bow difference and pitch deviation have been proposed, but in an actual light scanning device of a simultaneous scanning system, both bow difference and pitch deviation must be suppressed. Of the aforementioned technologies, only the technology disclosed in JP-A No. 7-209596 refers to both bow difference and pitch deviation.

The technology disclosed in JP-A No. 7-209596 is as shown in Fig. 12. Light beams 104, 106 emitted from laser diodes 100, 102 are incident on a rotary polygonal mirror A through a collimator lens 108 and a cylindrical lens 110. After the light beams 104, 106 incident on the rotary polygonal mirror A are reflected by the reflection surfaces of the rotary polygonal mirror A, they pass through an anamorphic motion compensation optical system (MCO) 112, 114 having an $f\theta$ lens, a cylindrical lens, and a cylindrical mirror, and leave the light scanning device in a state parallel to the system axis (optical system optical axis) 116. That is, occurrence of bow difference and pitch deviation is

suppressed by making the main exit beam of the light scanning device have a telecentric profile.

The cause of occurrence of bow difference in the plural-beam scanning optical system is, as mentioned above, that the light beam does not pass through the optical axis of the light beam. More specifically, the following two factors exist.

- Light beams are incident on a rotary polygonal mirror 200 at an angle with respect to the subscanning direction (see Fig. 13).

- Light beams pass outside of the optical axis of an $f\theta$ lens 202 when passing through the $f\theta$ lens 202 having power in the subscanning direction, or the beams enter the $f\theta$ lens 202 at an angle with respect to the subscanning direction (see Fig. 14).

In the technology disclosed in JP-A No. 7-209596, the interval between the light emission points (interval between laser diodes 100, 102) of the semiconductor laser array used as the light source is as narrow as 25 μm . Thus, there is no need to consider the angle in the subscanning direction on the rotary polygonal mirror A of the two light beams 104, 106 and the $f\theta$ lens of the anamorphic motion compensation optical system 112, 114, and both bow difference and pitch deviation can be decreased.

However, as is clear from Fig. 12, since the two light beams 104, 106 are incident on the rotary polygonal mirror A at different angles in the subscanning direction, when the interval between light emission points in the subscanning direction is large, the incident angle in the direction of the light beam on the rotary polygonal mirror A is large, and a bow

[illegible]

SUMMARY OF THE INVENTION

The present invention has been devised to solve the above problems, and it is an object thereof to present a light scanning method and light scanning device capable of decreasing the bow difference and pitch deviation, regardless of the interval in the subscanning direction between light emission points for output of beams, when scanning simultaneously by using plural beams.

To achieve this object, a first aspect of the invention is a light scanning method comprising the steps of: (a) making plural light beams emitted from a light source incident at least onto reflection surfaces of a deflector in a mutually parallel state in a direction orthogonal to a main scanning direction; (b) deflecting the plural light beams by the deflector; and (c) focusing the plural light beams deflected by the deflector on a surface to be scanned, with an afocal relation between the reflection surfaces of the deflector and the surface to be scanned in the direction orthogonal to the main scanning direction.

A second aspect of the invention is a light scanning device which deflects plural light beams emitted from a light source by making the light beams incident on reflection surfaces of a deflector, and scans the

beams are incident on the surface to be scanned can be suppressed, and also occurrence of pitch deviation at times when there is fluctuation in the distance between the reflection surfaces of the deflector and the surface to be scanned can be suppressed.

That is, according to the first and second aspects of the invention, occurrence of bow difference and pitch deviation at the time of scanning the surface to be scanned simultaneously by plural light beams can be suppressed (or decreased).

In a third aspect of the invention, the light source emits the plural light beams in a mutually parallel state, and the first optical system may sets an afocal and conjugate relation between the light source and the reflection surfaces of the deflector.

In this case, the first optical system comprises a collimator lens for making the light beams emitted from the light source as divergent luminous flux into substantially parallel luminous flux, and a cylinder lens having power for condensing in the direction orthogonal to the main scanning direction, and focusing the light beams made into substantially parallel luminous flux by the collimator lens as a line which is long in the main scanning direction on the reflection surfaces of the deflector. The collimator lens and cylinder lens may be disposed such that the focal position at the light beam advancing direction downstream side of the collimator lens substantially coincides with the focal position at the light beam advancing direction upstream side of the cylinder lens.

For correcting the tilt of the reflection surfaces of the deflector simultaneously, the second optical system may focus the plural light

beams deflected by the deflector on the surface to be scanned while setting a conjugate relation between the reflection surfaces of the deflector and the surface to be scanned.

In this case, the second optical system comprises an $f\theta$ optical system having power for condensing only in the main scanning direction, a first cylinder optical system having power for condensing in the direction orthogonal to the main scanning direction, and a second cylinder optical system having power for condensing in the direction orthogonal to the main scanning direction. The first cylinder optical system and second cylinder optical system are disposed such that the focal position at the light beam advancing direction downstream side of the first cylinder optical system substantially coincides with the focal position at the light beam advancing direction upstream side of the second cylinder optical system.

The power of the first cylinder optical system for condensing in the direction orthogonal to the main scanning direction may be smaller than the power of the second cylinder optical system for condensing in the direction orthogonal to the main scanning direction.

The light source may be a VCSEL array having plural light emission points disposed in a two-dimensional arrangement.

Therefore, the present invention results in the excellent effect of decreasing the bow difference and pitch deviation, regardless of the subscanning direction interval of light emission points for output of beams, when scanning simultaneously by using plural beams.

Fig. 8 is a block diagram showing an optical system from reflection surfaces of the rotary polygonal mirror to the photosensitive drum in a case in which the distance from the reflection surfaces of the rotary polygonal mirror to the first cylinder mirror is longer than the object side focal length of the first cylinder mirror.

Fig. 9 is a diagram for explaining bow difference.

Fig. 10 is a diagram for explaining pitch deviation.

Fig. 11 is a diagram for explaining a technique (of a prior art) for decreasing the bow difference and pitch deviation when using a light source having light emission points arranged in a row.

Fig. 12 is a block diagram showing a structure of an optical system for optically decreasing the bow difference and pitch deviation in the prior art.

Fig. 13 is a diagram for explaining factors for causing bow difference due to deflection by a rotary polygonal mirror.

Fig. 14 is a diagram for explaining factors for causing bow difference due to transmission through an $f\theta$ lens.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring now to the drawings, an example of a preferred embodiment of the present invention is described in detail below.

Fig. 1 shows a schematic structure of image forming apparatus 10. As shown in Fig. 1, the image forming apparatus 10 is covered with a casing 12.

An image forming section 14 is disposed in the casing 12. The

image forming section 14 includes a cylindrical photosensitive drum 16 rotating at a constant speed in the direction of arrow A shown in Fig. 1, and a light scanning device 18 for emitting light beams, while scanning, toward the photosensitive drum 16 (see arrow B in Fig. 1) on the basis of desired image data (gray scale image data in the present embodiment in which the image forming apparatus 10 is designed to form monochromatic images).

A charger 20 is disposed in a vicinity of the peripheral surface of the photosensitive drum 16. The charger 20 charges the photosensitive drum 16 uniformly. The photosensitive drum 16 uniformly charged by the charger 20 rotates in the direction of arrow A, and is irradiated with light beams from the light scanning device 18. Thus, a latent image is formed on the peripheral surface of the photosensitive drum 16.

In the rotating direction of the photosensitive drum 16, at the downstream side from the position of irradiating light beams by the light scanning device 18, a developer 22 for supplying toner to the photosensitive drum 16 is disposed, facing the circumferential surface of the photosensitive drum 16. The toner supplied from the developer 22 is applied to the portions irradiated with light beams from the light scanning device 18. As a result, a toner image is formed on the peripheral surface of the photosensitive drum 16.

In the rotating direction of the photosensitive drum 16, at the downstream side from the location of the developer 22 (a position beneath the axial center of the photosensitive drum 16), a charger for transfer 24 is disposed, facing the circumferential surface of the

mirror 52 is rotated at high speed in the direction of arrow D by a motor (not shown in the drawings).

The laser array 50 is a VCSEL having plural light emission points 54 disposed in a two-dimensional arrangement. Fig. 3 shows an example of this laser array 50. As shown in Fig. 3, the laser array 50 consists of a total of 36 light emission points 54 disposed in a two-dimensional arrangement, that is, six in the main scanning direction and six in the subscanning direction at specific intervals. The light emission points 54 arranged in the main scanning direction are shifted by one step each in the subscanning direction, which one step is equal to the distance between two light emission points 54 adjacent in the subscanning direction divided into six equal sections. That is, as far as the subscanning direction is concerned, a light emission point 54 is disposed at each step. By thus shifting the light emission points 54 in the subscanning direction, all light emission points 54 can scan different scanning lines (so that 36 scanning lines can be scanned simultaneously).

From each light emission point 54 of the laser array 50, a light beam LB modulated according to desired image data is emitted. Since the laser array 50 is a VCSEL, plural light beams LB are emitted in parallel (not as parallel light, but as light beams having the same advancing direction).

At the downstream side in the advancing direction of the plural light beams LB emitted from the light emission points 54, as shown in Fig. 2, a collimator lens 56, an aperture 58, a cylinder lens 60, and a mirror 61 are disposed sequentially. The plural light beams LB emitted from the

light emission points 54 pass through the collimator lens 56, aperture 58, cylinder lens 60, and mirror 61, and reach the rotary polygonal mirror 52.

The collimator lens 56 transforms the plural light beams LB emitted from the light emission points 54 from divergent light to substantially parallel light, and converges the light beams to intersect at the focal position at the image side of the collimator lens 56 (light beams advancing direction downstream side).

The aperture 58 is disposed at the image side focal position of the collimator lens 56. The plural light beams LB transformed into substantially parallel light by the collimator lens 56 pass through the aperture 58, and are shaped at the same time. At the location of the aperture 58, since all light beams LB intersect, shaping by the aperture 58 is the same for all light beams LB.

The cylinder lens 60 has power only in the subscanning direction, and the plural light beams LB converge in the subscanning direction individually by the cylinder lens 60, and are reflected by the mirror 61, and guided to the rotary polygonal mirror 52.

The cylinder lens 60 is also disposed such that the object side (light beam advancing direction upstream side) focal position of the cylinder lens coincides with the location of the aperture 58, and such that the image side focal position is located on the reflection surface 52A of the rotary polygonal mirror 52.

By disposing the cylinder lens 60 in this way, the laser array 50 and the reflection surface 52A of the rotary polygonal mirror 52 are set in an afocal and conjugate relation in the subscanning direction. Therefore,

the plural light beams LB are individually focused as linear images on the reflection surface 52A of the rotary polygonal mirror 52 in the subscanning direction, and also are incident, in parallel in the subscanning direction, on the reflection surface 52A of the rotary polygonal mirror 52 without forming an angle in the subscanning direction with respect to the reflection surface 52A of the rotary polygonal mirror 52.

The plural light beams incident on the rotary polygonal mirror 52 are deflected by rotation of the rotary polygonal mirror 52 while the incident angle of the light beams on each reflection surface 52A is changed continuously. As a result, the plural light beams LB are emitted while scanning the surface of the photosensitive drum 16 simultaneously in the direction of arrow E (main scanning direction).

In the advancing direction of the light beams LB reflected by the reflection surfaces 52A of the rotary polygonal mirror 52, there is an $f\theta$ lens 62 composed of first lens 62A and second lens 62B, having power only in the main scanning direction. By this $f\theta$ lens 62, the scanning speed becomes uniform when the photosensitive drum 15 is irradiated with each light beam LB.

At the downstream side in the advancing direction of the light beam from the $f\theta$ lens 62, a first cylinder mirror 64A having power only in the subscanning direction is disposed. In the reflecting direction of the light beam LB by the first cylinder mirror 64A, a second cylinder mirror 64B having power only in the subscanning direction is disposed. By the first cylinder mirror 64A and second cylinder mirror 64B, each

light beam LB is guided to the photosensitive drum 16, and focused on the circumferential surface of the photosensitive drum 16.

The first cylinder mirror 64A and second cylinder mirror 64B are disposed so that the image side focal position of the first cylinder mirror 64A and the object side focal position of the second cylinder mirror 64B coincide with each other (that is, the optical path length between the two mirrors is the sum of the focal length of the first cylinder mirror and the focal length of the second cylinder mirror). Thus, the reflection surface 52A of the rotary polygonal mirror 52 and the scanning position on the peripheral surface of the photosensitive drum 16 are in an afocal and conjugate relation in the subscanning direction.

However, the first cylinder mirror 64A and second cylinder mirror 64B are both required to have a positive power (that is, a condensing power, and the greater this power, the shorter is the focal length). In a positive-negative or negative-positive combination, an afocal and conjugate relation cannot be established. Note that in the following explanation, both the cylinder mirror 64A and the cylinder mirror 64B are called the cylinder mirror 64 if it is not required to distinguish between the first and second cylinder mirrors 64A, 64B particularly.

The operation of the present embodiment is explained below with reference to Fig. 4.

Plural (36 arranged in the subscanning direction) light beams emitted from the light emission points 54 of the laser array 50 are made into substantially parallel light by means of the collimator lens 56, shaped

by the aperture 58, and converge in the subscanning direction by means of the cylinder lens 60, and are incident on the reflection surfaces 52A of the rotary polygonal mirror 52. The plural light beams incident on the rotary polygonal mirror 52 are deflected by rotation of the rotary polygonal mirror 52.

At this time, since the laser array 50 and reflection surface 52A of the rotary polygonal mirror 52 are in an afocal and conjugate relation, the plural light beams emitted from the light emission points 54 are incident on the reflection surfaces 52A of the rotary polygonal mirror 52, in a mutually parallel state (in the same advancing direction), and without forming an angle in the subscanning direction with respect to the reflection surfaces 52A of the rotary polygonal mirror 52. That is, the plural light beams are incident on the reflection surfaces 52A of the rotary polygonal mirror 52 in a manner parallel to the optical axis L1 of the optical system of the light scanning device 18. As a result, occurrence of bow difference due to deflection of the light beams LB on the rotary polygonal mirror 52 can be suppressed.

The plural light beams LB deflected by rotation of the rotary polygonal mirror 52 enter the $f\theta$ lens 62 in a mutually parallel state. The plural light beams LB entering the $f\theta$ lens 62 are controlled to have an uniform scanning speed when the light beams are scanned onto the peripheral surface of the photosensitive drum 16. This $f\theta$ lens 62 has power only in the main scanning direction, and bow difference is not caused if the plural light beams LB pass through the $f\theta$ lens 62.

The plural light beams passing through the $f\theta$ lens 62 are focused

the photosensitive drum 16 is 360 mm, and the relation with the focal length of the first cylinder mirror 64A and second cylinder mirror 54B disposed therebetween is as shown in Table 1.

μm), the bow difference and pitch deviation can be suppressed, and the image can be written at high speed and high writing density (240 dpi) by scanning simultaneously with plural light beams.

The cylinder mirror 64 (especially the second cylinder mirror 64B) is disposed after the rotary polygon mirror 52 in the direction in which light advances, and reflects the deflected and scanned light beams, and is hence large in length. For reducing the size of the light scanning device 18, it is desired to shorten the length of the cylinder mirror 64, and it is necessary for this purpose to dispose the cylinder mirror 64, especially the second cylinder mirror 64B, apart from the photosensitive drum 16 as far as possible.

Besides, if the second cylinder mirror 64B is close to the photosensitive drum 16, the beam diameter on the mirror is small, and flaws or stains on the mirror surface may have effects on the focusing state of the light beams LB (flaws or stains appear in an enlarged manner). To decrease the effects of flaws or stains, it is preferred that the second cylinder mirror 64B be disposed apart from the photosensitive drum 16 as far as possible. On the other hand, for reducing the size of the image forming apparatus 10, it is desired that the light scanning device 18 and the photosensitive drum 16 be disposed as closely to each other as possible, and there may be a limit to the distance (the optical path length) between the rotary polygonal mirror 52 and the photosensitive drum 16.

Accordingly, without changing the distance (optical path length) between the rotary polygonal mirror 52 and the photosensitive drum 16 and the conjugate magnification (writing density in the subscanning

direction), examples of changing the distance (optical path length) between the second cylinder mirror 64B and the photosensitive drum 16 are shown in Table 2. In the examples shown in Table 2, the optical path length between the rotary polygonal mirror 52 and the photosensitive drum 16 is 360 mm, and the conjugate magnification between the rotary polygonal mirror 52 and photosensitive drum 16 is -0.5.

Table 2

No	Focal length of first cylinder mirror (mm)	Focal length of second cylinder mirror (mm)	Conjugate magnification	Optical path length between rotary polygonal mirror and first cylinder mirror (mm)	Optical path length between first and cylinder mirrors (mm)	Optical path length between second cylinder mirror and photosensitive drum (mm)
1	100	50	-0.5	180.346633	150	29.65337
2	110	55	-0.5	150.346633	165	44.65337
3	120	60	-0.5	120.346635	180	59.65337
4	130	65	-0.5	90.346638	195	74.65336
5	140	70	-0.5	60.346641	210	89.65336
6	150	75	-0.5	30.346644	225	104.6534

have power in the subscanning direction, in order to decrease the image curvature in the subscanning direction to an extent that does not present problems in practice, it is desired to set the conjugate relation of the rotary polygonal mirror 52 and the photosensitive drum 16 in a reducing system (conjugate magnification < 1), that is, the focal length of the second cylinder lens is shorter than the focal length of the first cylinder lens 60.

In this example, the optical system is composed of the $f\theta$ lens, first cylinder mirror and second cylinder mirror, but the present invention is not limited to this example. Instead of the $f\theta$ lens, an $f\theta$ mirror may be used, or at least one of the first and second cylinder mirrors may be replaced by a cylinder lens.

In the present embodiment, the light scanning device 18 according to the invention is used in the image forming apparatus 10, but the present invention is not limited to this embodiment alone. The present invention may be applied to any image forming apparatus for forming an image by scanning light beams.